

Gauge Size

535 KCMIL			
PRODUCT NAME	CABLE TYPE	NO. OF CONDUCTORS	PAGE
Super-Trex® Single Conductor Power Cable	Power	1	39
Super-Trex® Variable Frequency Drive Shielded Power Cable	VFD	3	47
646 KCMIL			
Super-Trex® Single Conductor Power Cable	Power	1	39
750 KCMIL			
Super-Trex® Type SH Single Conductor Power Cable	Medium Voltage	1	42
777 KCMIL			
Super-Trex® Single Conductor Power Cable	Power	1	39

Ratings

RATING	PAGE
ANSI TIA/EIA 568-B	50, 71, 73
Antimicrobial	102
ASTM B-33	42
AWM	51-52, 69
CE	48-49, 58, 60-61, 82, 94
Corona Resistant to 2,000 V	47-49
CSA	29-31, 35-37, 46-46, 48-49, 53, 56-57, 61-68, 87-88, 97-105, 112, 118-119
CSA – 1,000 V	48-49
cUL	32-34, 47, 75, 123
Direct Burial	41
EIA RS-232/422/485	70
Extra Hard Usage	29-31, 34-35, 38, 56
For CT Use	39
Frequency Range up to 500 MHz	72
Frequency Range up to 1000 MHz	50, 71
FT-1 Flame Rating	30-32, 37, 45-46, 51-54, 57, 61-68, 97, 99-105, 123
FT-2 Flame Rating	77, 119
FT-4 Flame Rating	29, 36, 42, 48-49, 58-60, 80-82
FT-5 Flame Rating	33, 35, 56
Halogen-Free Flame Retardant	71-73
ICEA S-75-381	33-34
ICEA S-75-381/NEMA WC-58	42
IEC 60332-1	50, 71-72
IEC 61156-5	75
IEC 61156-6	50, 71-72
IEEE - 383 Flame Rating	42
IEEE 1202 Flame Rating	33, 39, 41
ISO/IEC 11801	50, 71, 72

Ratings

RATING	PAGE
Low Smoke Zero Halogen	119
MSHA Approved	29, 31, 33-35, 45, 53, 56, 62, 66
ODVA Conformity	77, 80-88
RoHS Compliant	29-32, 36-39, 42, 45-46, 48-50, 53, 57-73, 77-78, 80-91, 94-97, 99-107, 110-112, 114-116, 118-123, 125-127, 132
Suitable for Class 1, 2, Division 2	36, 48-49, 52-53, 57, 58-60
Suitable for Class 1, 2, 3, Division 1 & 2	29-31, 33-35, 38, 56
Suitable for Class 1, 2, 3, Division 2	98
Sunlight Resistant	39, 41, 48-49, 75, 94
TIA / EIA 568-C-2	73
TIA / EIA 568-B-2 CAT6	74
Type PLTC	80-82
Type RHH/RHW	38-39
Type SC	45
Type SOOW	29-31
Type TC	57
Type TC – 600 V	53
Type TC-ER	29, 47, 52
Type TC-ER – 600 V	36, 48-49, 58-60
Type TC-ER – 2,000 V	34
Type W	35, 56
Type W – 2,000 V	33-34, 38
Type WTTC – 1,000 V	53
UL 2225	29
UL Listed	29-31, 33-36, 38-41, 45, 47-49, 52-54, 56-60, 75, 87-88, 98
UL Recognized	32, 37, 51, 61-70, 73, 77-82, 94, 97, 99-105, 111-112, 115, 117-119, 123
UV Resistant	29-34, 36, 38, 45-46, 53, 73, 123,133
VW-1 Flame Rating	39, 52, 62-70, 97, 99, 102-105, 117