


7 Pin Molded Valve Plugs

- RoHS Compliant
- Straight and 90° Configurations

The 7-Pin Molded Valve Plug is available in a straight or 90° head with no assembly required. Each connector head is protected with an O-ring seal and coupling nut with machined hole for tie down. Used with Atos, Moog, Vickers and Rexroth servo or proportional valves.



FEATURES & BENEFITS

- 1. TREX-ONICS® OVERALL SHIELDED CONTINUOUS FLEX MULTI-CONDUCTOR CABLE** — Superior performance in continuous flex applications. TPC’s unique cable 18/6* shielded design has been tested to over 25 million cycles without electrical failure.
- 2. O-RING SEAL** — Each connector head is protected with an o-ring seal. The o-ring compresses when tightened, sealing the connector end from contaminants.
- 3. 90° OR STRAIGHT CONSTRUCTION** — Select the proper configuration for the application.
- 4. PUR MOLDED HEAD DESIGN** — Rugged polyurethane head is molded to the Trex-Onics® cable to provide a sealed connection, eliminating the risk of failure due to contaminants.
- 5. COUPLING NUT WITH MACHINED HOLE** — Hole can be used to tie down coupling ring and eliminate possible loosening caused by vibration and constant movement. Insures a secure connection in the toughest environments.
- 6. THREAD** — 7/8" – 20"

APPLICATIONS

- Used with Atos, Moog, Vickers and Rexroth servo or proportional valves.

ORDERING INFORMATION (MINIMUM PURCHASE MAY BE REQUIRED IF PRODUCT NOT STOCKED)

PART NO.		DESCRIPTION	LENGTH (FT)
STRAIGHT	90°		
77003	77903	7 Pin Female Plug	3
77006	77906	7 Pin Female Plug	6
77009	77909	7 Pin Female Plug	9
77012	77912	7 Pin Female Plug	12
77015	77915	7 Pin Female Plug	15
77020	77920	7 Pin Female Plug	20
77050	77950	7 Pin Female Plug	50
77060	77960	7 Pin Female Plug	60

* Part number 61406 page # 62