

Hoffman Products' Ferrules

- No More Frayed or Broken Wires
- Tin Plated Copper Barrel with Nylon Insulation
- 105°C (221°F)
- 300 Volts

High quality Speed-Ease™ tin plated ferrules are available in non-insulated or insulated styles for use in terminal blocks to avoid direct contact with wire and avoid the possibility of wire strand breakage. Available in wire sizes 26-2/0 AWG.

SINGLE INSULATED FERRULES



PART NO.	WIRE SIZE	COLOR
FEB268	26 AWG	LIGHT BLUE
FEV268	26 AWG	VIOLET
FEB248	24 AWG	TURQUOISE
FEP248	24 AWG	PINK
FEO228	22 AWG	ORANGE
FEW228	22 AWG	WHITE
FEB208	20 AWG	BLUE
FEW208	20 AWG	WHITE
FEG208	20 AWG	GRAY
FER188	18 AWG	RED
FEY188	18 AWG	YELLOW
FEBK168	16 AWG	BLACK
FER168	16 AWG	RED
FEG148	14 AWG	GRAY
FEB148	14 AWG	BLUE
FEO1212	12 AWG	ORANGE
FEG1212	12 AWG	GRAY
FEGN1012	10 AWG	OLIVE
FEBK1012	10 AWG	BLACK
FEY1012	10 AWG	YELLOW
FEBR812	8 AWG	BROWN
FEI812	8 AWG	IVORY
FER812	8 AWG	RED
FEI612	6 AWG	IVORY
FEGN612	6 AWG	GREEN
FEB612	6 AWG	BLUE
FEBK416	4 AWG	BLACK
FEY416	4 AWG	YELLOW
FER216	2 AWG	RED
FEB1/020	1/0 AWG	BLUE
FEGN1/020	1/0 AWG	OLIVE
FEY2/020	2/0 AWG	YELLOW

NON-INSULATED FERRULES



PART NO.	WIRE SIZE
FE226	22 AWG
FE206	20 AWG
FE186	18 AWG
FE167	16 AWG
FE147	14 AWG
FE1212	12 AWG
FE1010	10 AWG
FE815	8 AWG
FE615	6 AWG
FE418	4 AWG
FE1/022	1/0 AWG
FE2/025	2/0 AWG
FE3/025	3/0 AWG